RY-CS Crawler Scissor Lifts

Compare the five model configurations below. Check the selected model and its operating limits before ordering.

Specification	RY-CS0608	RY-CS0810	RY-CS1012	RY-CS1214	RY-CS1416
Working height	8 m	10 m	12 m	14 m	15.8 m
Platform height	6 m	8 m	10 m	12 m	13.8 m
Rated platform load	450 kg	450 kg	320 kg	320 kg	227 kg
Platform size (L x W)	2.27 x 1.13 m	2.27 x 1.13 m	2.27 x 1.13 m	2.27 x 1.13 m	2.63 x 1.13 m
Lift pump motor	48 V / 4.5 kW	48 V / 4.5 kW	48 V / 4.5 kW	48 V / 4.5 kW	48 V / 4.5 kW
Electric travel motor	48 V / 4 kW	48 V / 4 kW	48 V / 4 kW	48 V / 4 kW	48 V / 4 kW
Battery configuration	8 x 6 V / 220 Ah	8 x 6 V / 220 Ah	8 x 6 V / 220 Ah	8 x 6 V / 220 Ah	8 x 6 V / 240 Ah
Charger output	48 V / 30 A	48 V / 30 A	48 V / 30 A	48 V / 30 A	48 V / 30 A

Charging: the charger figures above are DC output ratings. Confirm site mains input voltage, frequency and plug type separately.

Selection and transport: request the full configuration sheet, transport dimensions, machine weight, site suitability and operating instructions for the selected model. This comparison is not an operating manual or a certificate.

View model details and request a quotation